

C € 0085



CERT

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085AQ0883

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	MEDENUS Gas-Druckregeltechnik GmbH Saßmicker Hammer 40, D-57462 Olpe
Distributor <i>Vertreiber</i>	MEDENUS Gas-Druckregeltechnik GmbH Saßmicker Hammer 40, D-57462 Olpe
Product Category <i>Produktart</i>	gas fittings: Pressure regulator for natural gas and all-gas (4301)
Product Description <i>Produktbezeichnung</i>	Pressure regulator optional with safety shut-off valve (SAV) for upper and lower shut down pressure and/or pilot support
Model <i>Modell</i>	R/RS/RP/RSP 251, R/RS/RP/RSP 255
Countries of Destination <i>Bestimmungsländer</i>	European Union
Test Reports <i>Prüfberichte</i>	type testing: 17/304/4301/210 from 21.12.2017 (EBI) type testing: 16/180/4301/210 from 18.07.2016 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 334 (01.07.2009) DIN EN 14382 (01.07.2009)

Validity / File no. 21.04.2018 until 05.03.2028 / 17-0815-GEA
Gültigkeit / AZ

05.03.2018 Rie A-1/2

Dale, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases and non-aggressive gases	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
R/RS/RP/RSP 251, R/RS/RP/RSP 255	nominal diameter: DN 50	
R/RS/RP/RSP 251, R/RS/RP/RSP 255	nominal diameter: DN 80	
R/RS/RP/RSP 251, R/RS/RP/RSP 255	nominal diameter: DN 100	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
R	pressure regulator
RS	pressure regulator with SAV
RP	pressure regulator with pilot support (pilots R70-10, R70-20, R70-100 and for the SAV K70-10)
RSP	pressure regulator with SAV and pilot support
R/RS/RP/RSP 251	max allowable pressure PS = 8 bar, nominal pressure PN 8
R/RS/RP/RSP 255	max allowable pressure PS = 16 bar, nominal pressure PN 16
R/RS/RP/RSP 251; R/RS/RP/RSP 255	temperature range: -20°C to 60°C, class 2

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

connections: on both sides flanges PN 16 according to DIN EN 1092-4 or ASME B 16.5 class 150 RF
Accuracy class AC/ lock up pressure group SG for pressure regulator without pilot:
18...100 mbar: AC 10/SG 20
100...500 mbar: AC 5/SG 10
500...1500 mbar: AC 2,5/SG 10
>1000 mbar: AC 5/ SG 10 (only with regulation device 205/275-2)
Accuracy class AC/ lock up pressure group SG for pressure regulator with pilot:
10...20 mbar: AC 10/SG 50
20...50 mbar: AC 5/SG 20
50...500 mbar: AC 5/SG 10
500...2500 mbar: AC 2,5/SG 10
2500...5000 mbar: AC 1/SG 10
>5000 mbar: AC 1/SG 5
upper accuracy group AG of the SAV:
50...100 mbar: AG 10
100...500 mbar: AG 5
>500 mbar: AG 2,5
lower accuracy group AG of the SAV:
10...30 mbar: AG 20
30...50 mbar: AG 10
>50 mbar: AG 5